

NEON USER GUIDE TO BATHYMETRIC AND MORPHOLOGICAL MAPS (DP4.00132.001)

PREPARED BY	ORGANIZATION
Brandon Jensen	AQU
Caren Scott	AQU
Stephanie Parker	AQU
Kaelin M. Cawley	AQU
Zachary L. Nickerson	AQU



CHANGE RECORD

REVISION	DATE	DESCRIPTION OF CHANGE
А	07/17/2018	Addition of Data Variables Information
В	05/25/2020	Included general statement about usage of neonUtilities R package and statement about possible location changes. Updated taxonomy information.
B.1	04/20/2021	Updated information on the data tables published in this data prod- uct that are not involved with the interannual geomorphology surveys (AIS site survey data). Removed information on the data tables that are no longer published in this data product, but are now published in the Stage-discharge rating curves (DP4.00133.001) and Continuous discharge (DP4.00130.001) data products.
С	03/02/2022	Updated information on data package contents for suveys produced with the Biosonics MX echosounder rather than the Humminbird models. Updated section 4.3 Data Revision with latest information regarding data release.



TABLE OF CONTENTS

1	DESC	CRIPTION	1
	1.1	Purpose	1
	1.2	Scope	1
2	RELA	TED DOCUMENTS AND ACRONYMS	2
	2.1	Associated Documents	2
	2.2	Acronyms	3
3	DATA	A PRODUCT DESCRIPTION	4
	3.1	Spatial Sampling Design	4
	3.2	Temporal Sampling Design	5
	3.3	Variables Reported	5
	3.4	Spatial Resolution and Extent	6
	3.5	Temporal Resolution and Extent	6
	3.6	Associated Data Streams	6
	3.7	Product Instances	7
	3.8	Data Relationships	7
	3.9	Special Considerations	11
		3.9.1 Downloading Bathymetric and Morphology Data	11
4	DATA	A QUALITY	12
	4.1	Data Entry Constraint and Validation	12
	4.2	Manual Data Processing Steps	12
	4.3	Data Revision	12
	4.4	Uncertainty	12
	4.5	Quality Flagging	14

LIST OF TABLES AND FIGURES

Table 1	Suite of L4 Data Products Associated with the Bathymetric (BATH) and Morphologi-	
cal F	labitat (НАВ) Мар	7



Table 2	Maps produced from surveys collected prior to 2020: List of Variables Provided	
with	the Bathymetric (BATH), Morphological Habitat (HABITAT) Map, Survey Tracks	
(BAT	H_Tracks), and Shoreline (BATH_shorePolyDigitized) File Types. 'DxxSITE' represents	
the M	NEON Domain number for each File Type, for example: D03BARC	9
	Maps produced from surveys collected beginning in 2020: List of Variables Pro- d with the Bathymetric (BATH), Morphological Habitat (HABITAT) Map, Survey Tracks H_Tracks), and Shoreline (BATH_shorePolyDigitized) File Types. 'DxxSITE' represents	
the M	NEON Domain number for each File Type, for example: D03BARC	10
Table 4	Options for dataQF and their explanations	14
Figure 1 the s	Schematic of survey pattern undertaken in the vessel for (a) lake grid survey, with shoreline (in red), and island as well as (b) non-wadeable stream survey pattern.	5



1 DESCRIPTION

1.1 Purpose

This document provides an overview of the data included in this NEON Level 4 data product, the quality controlled product generated from raw Level 0 data, and associated metadata. In the NEON data products framework, the raw data collected in the field, for example, the dry weights of litter functional groups from a single collection event are considered the lowest level (Level 0). Raw data that have been quality checked via the steps detailed herein, as well as simple metrics that emerge from the raw data are considered Level 4 data products.

The text herein provides a discussion of measurement theory and implementation, data product provenance, quality assurance and control methods used, and approximations and/or assumptions made during L4 data creation.

1.2 Scope

This document briefly describes the steps needed to generate the L4 data product Bathymetric and Morphological Maps - and associated metadata from input data, for a more detailed description refer to NEON Standard Operating Procedure: Post-Processing of Bathymetric and Side Scan Sonar Data from NEON Lakes and Non-Wadeable Streams, NEON.DOC.004856 (AD[09]). This document also provides details relevant to the publication of the data products via the NEON data portal, with additional detail available in the file, NEON Data Variables for Bathymetric and Morphological Maps (DP4.00132.001) (AD[05]), provided in the download package for this data product.

This document describes the process for ingesting and performing automated quality assurance and control procedures on the data collected in the field pertaining to AOS Protocol and Procedure: Bathymetry and Morphology of Lakes and Non-Wadeable Streams (AD[07]). The raw data that are processed in this document are detailed in the file, NEON Raw Data Validation for Bathymetric and Morphological Maps (DP0.00132.001) (AD[04]), provided in the download package for this data product. Please note that raw data products (denoted by 'DP0') may not always have the same numbers (e.g., '10033') as the corresponding L4 data product.



2 RELATED DOCUMENTS AND ACRONYMS

2.1 Associated Documents

AD[01]	NEON.DOC.000001	NEON Observatory Design (NOD) Requirements
AD[02]	NEON.DOC.001152	NEON Aquatic Sampling Strategy
AD[03]	NEON.DOC.002652	NEON Data Products Catalog
AD[04]	Available with data download	Validation csv
AD[05]	Available with data download	Variables csv
AD[06]	NEON.DOC.001152	NEON Aquatic Sampling Strategy
AD[07]	NEON.DOC.001197	AOS Protocol and Procedure: Bathymetry and Morphology of Lakes and Non-Wadeable Streams
AD[08]	NEON.DOC.004825	NEON Algorithm Theoretical Basis Document: OS Generic Transi- tions
AD[09]	NEON.DOC.004856	NEON Standard Operating Procedure: Post-Processing of Bathy- metric and Side Scan Sonar Data from NEON Lakes and Non- Wadeable Streams
AD[10]	NEON.DOC.000008	NEON Acronym List
AD[11]	NEON.DOC.000243	NEON Glossary of Terms
AD[12]	Available on NEON data portal	NEON Ingest Conversion Language Function Library
AD[13]	Available on NEON data portal	NEON Ingest Conversion Language
AD[14]	Available with data download	Categorical Codes csv



2.2 Acronyms

Acronym	Definition
DGPS	Differential Global Positioning System
EBK	Empirical Bayesian Kriging
GIS	Geographic Information System
GPS	Global Positioning System
MODIS	Moderate Resolution Imaging Spectroradiometer
NDVI	Normalized Difference Vegetation Index
NICL	NEON's Ingest Conversion Language
m	Meter
km	Kilometer
WAAS	Wide Area Augmentation System
WebUI	Web user Interface



3 DATA PRODUCT DESCRIPTION

The Bathymetric and Morphological Map data product (DP4.00132.001) provides depths of lakes and non-wadeable streams (rivers), sediment and substrate characteristics, as well as the presence or absence, approximate abundance, distribution, and size of underwater flora. All data following processing are reported at the spatial resolution of a single latitude (x), longitude (y), elevation (depth; z), and date/time of a single collection event.

Maps produced from surveys collected prior to 2020: High accuracy depth (bathymetric) maps are obtained using a suite of hydroacoustic instrumentation interfaced with a differential global positioning system (DGPS) mounted on a vessel. The Wide Area Augmentation System (WAAS) is a form of DGPS that provides enhanced position accuracy (<3 m). Acoustic images of biota, substrate, and benthic structures are obtained with sonar which are georeferenced and mosaic in post-processing. The resulting master mosaic imagery coupled with ground truth observations are used to classify the substrate type and benthic habitat features. These may include sand, silt, clay, boulder, bedrock, and large woody debris. Summary data include volume and area calculations at specific bathymetric intervals or whole body of water estimates as well as areal calculations of habitat features.

Maps produced from surveys collected beginning in 2020: High accuracy depth (bathymetric) maps are obtained using a single-beam, down looking sonar unit and on-board GPS unit. The sonar data was processed alongside ground truth observations to create bathymetric maps and classify the substrate type and benthic habitat features. These may include sand, silt, clay, boulder, bedrock, and large woody debris. Summary data include volume and area calculations at specific bathymetric intervals or whole body of water estimates as well as areal calculations of habitat features.

3.1 Spatial Sampling Design

Bathymetric and morphological surveys are executed at NEON lakes and non-wadeable streams. A vesselmounted acoustic sonar system and GPS is driven along the shoreline as well as across lake sites in a gridded pattern (Figure 1). Bathymetric surveys cover the entire lake with transects spaced up to 35 m apart. At non-wadeable stream sites, the vessel is driven in a series of tracks parallel to shore and in zig-zag patterns (Figure 1) also up to 35 m apart, and covers the entire permitted reach of approximately 1 km.

As much as possible, sampling occurs in the same locations over the lifetime of the Observatory. However, over time some sampling locations may become impossible to sample, due to disturbance or other local changes. When this occurs, the location and its location ID are retired. A location may also shift to slightly different coordinates. Refer to the locations endpoint of the NEON API for details about locations that have been moved or retired: https://data.neonscience.org/data-api/endpoints/locations/





Figure 1: Schematic of survey pattern undertaken in the vessel for (a) lake grid survey, with the shoreline (in red), and island as well as (b) non-wadeable stream survey pattern.

3.2 Temporal Sampling Design

Bathymetric surveys at lakes and non-wadeable streams are completed at a minimum of every 5 years during biological sampling bout 2 and during the period of peak greenness, defined as the range of dates where Moderate Resolution Imaging Spectroradiometer (MODIS) Normalized Difference Vegetation Index (NDVI) is within 90% of the local seasonal maximum (AD[02]). If an extreme event results in substantial physical change to the morphology or submerged habitat, an out-of-cycle survey may be requested. It is recommended that subsequent sampling events are scheduled to occur +/- 2 weeks of first sampling event when practicable. The survey duration will vary for each site based on water body area (size) and seasonal conditions (wind, lightning, etc.). It is advised that surveys are started as early in the day as possible to complete the survey. Surveys that take longer than one day to complete will resume the following day. Typically, non-wadeable stream sites are surveyed in one day; however, lake sites can take up to five days. If field conditions deteriorate, then survey dates may not be consecutive in order to allow for more ideal conditions.

3.3 Variables Reported

All variables reported from the field (L0 data) are listed in the file, NEON Raw Data Validation for Bathymetric and Morphological Maps (DP0.00132.001) (AD[04]). All variables reported in the published data (L4 data) are also provided separately in the file, NEON Data Variables for Bathymetric and Morphological Maps (DP4.00132.001) (AD[05]).

Field names have been standardized with Darwin Core terms (http://rs.tdwg.org/dwc/; accessed 12 December 2017), the Global Biodiversity Information Facility vocabularies (http://rs.gbif.org/vocabulary/ gbif/; accessed 12 December 2017), the VegCore data dictionary (https://projects.nceas.ucsb.edu/nceas/ projects/bien/wiki/VegCore; accessed 12 December 2017), where applicable. NEON AOS spatial data employs the World Geodetic System 1984 (WGS84) for its fundamental reference datum and Geoid12A for its reference gravitational ellipsoid. Latitudes and longitudes are denoted in decimal notation to six decimal places, with longitudes indicated as negative west of the Greenwich meridian.



Some variables described in this document may be for NEON internal use only and will not appear in downloaded data.

3.4 Spatial Resolution and Extent

Maps produced from surveys collected prior to 2020: Raw side-scan and down-imaging sonar data are recorded using a dual-beam echosounder at a frequency of 200/83 kilohertz at beam angles of 6° and 19°. It is combined with WAAS GPS technology which increases the horizontal accuracy.

Maps produced from surveys collected beginning in 2020: Raw sonar data are recorded using a singlebeam, downlooking echosounder at a frequency of 200 kilohertz with a 9° beam cone and onboard DGPS.

Water depths are determined by the first echosounder return and is based on the speed of sound in water and compensated for temperature. The second echo return provides an indication of bottom hardness. More intense returns are suggestive of rocky and compacted sediment where as low intensity returns may indicate soft sediment, vegetation, or fish. The shoreline at the time of sampling is mapped with a handheld GPS receiver with decimeter accuracy (Trimble) in continuous mode.

The finest scale at which spatial bathymetric data are reported are at a single point (latitidue and longitude) and associated depth for NEON lakes and 1,000 m reaches of NEON non-wadeable streams. In postprocessing, the collected point locations and depth contours are constructed using the Empirical Bayesian Kriging (EBK) model parameters for interpolating depth data points in a Geographic Information System (GIS).

3.5 Temporal Resolution and Extent

The finest temporal resolution at which bathymetric and morphological data are reported is the **endDate**, a single date on which survey data were collected. Bathymetric and morphological surveys are conducted at each lake and non-wadeable stream site once every five years. Should an extreme event result in significant changes in water level, morphology, or habitat, an additional survey may be conducted following a request, once safe conditions allow.

The NEON Data Portal currently provides data in monthly files for query and download efficiency. Queries including any part of a month will return data from the entire month. Code to stack files across months is available here: https://github.com/NEONScience/NEON-utilities

3.6 Associated Data Streams

At river sites and flow-through lake inflow and outflow locations, cross-section survey data measured at the stream-discharge transect, staff gauge elevation measured during AIS surveys, and rating curve identification metadata can be associated with the Stage-discharge rating curves (DP4.00133.001) data product and Continuous discharge (DP4.00130.001) data product in order to identify, assess, and/or validate potential shifts in stage-discharge relationships at given sites and to relate streamflow to stage level, respectively.



3.7 Product Instances

A minimum of one bathymetric survey will be conducted at each NEON lake and non-wadeable stream site every five years. Additional surveys will occur if an extreme event results in substantial physical change to the morphology or submerged habitat. Each sampling event will yield several post-processed data files for bathymetric and morphological data described in (Table 1).

3.8 Data Relationships

The basic spatial data that are part of the bathymetric and morphological data product are described in Table 1. Please see Section 3.8.1 Downloading Bathymetric and Morphology Data for information on accessing these data. Variables associated with the collected and published data are described in (Table 2 & Table 4). All NEON Aquatic Observation System sampling locations can be found in the respective Domain Aquatic Site Sampling Design (e.g, Aquatic Site Sampling Design - NEON Domain ##) in the NEON Document Library, Science Designs folder (http://data.neonscience.org/documents).

Data downloaded from the NEON Data Portal are provided in separate data files for each site and month requested. The neonUtilities R package contains functions to merge these files across sites and months into a single file for each table described above. The neonUtilities package is available from the Comprehensive R Archive Network (CRAN; https://cran.r-project.org/web/packages/neonUtilities/index.html) and can be installed using the install.packages() function in R. For instructions on using neonUtilities to merge NEON data files, see the Download and Explore NEON Data tutorial on the NEON website: https://www.neonscience.org/download-explore-neon-data

Table 1: Suite of L4 Data Products Associated with the Bathymetric (BATH) and Morphological Habitat (HAB) Map.



File Type	Description	
BATH Contour.shp	Contour depth lines at a specific interval main shapefile	
BATH Contour.shx	Contour depth lines index file (required for .shp to open)	
BATH Contour.dbf	Contour depth lines dBASE attribute file (required for .shp to open)	
BATH Contour.prj	Contour depth lines projection definition file (required for .shp to open)	
BATH Contour.xml	Contour depth lines Extensible Markup Language metadata (optional for .shp to open)	
BATH Contour.sbn	Contour depth lines spatial index file for optimizing spatial queries (optional for .shp to open)	
BATH Contour.sbx	Contour depth lines spatial index file for optimizing loading time (optional for .shp to open)	
BATH Contour.cpg	Contour depth lines encoded plain text file describes .shp text charac- ter set (optional for .shp to open)	
BATH Shoreline.shp	Shoreline boundary of water body main shapefile	
BATH Shoreline.shx	Shoreline boundary index file (required for .shp to open)	
BATH Shoreline.dbf	Shoreline boundary dBASE attribute file (required for .shp to open)	
BATH Shoreline.prj	Shoreline boundary projection definition file (required for .shp to open)	
BATH Shoreline.xml	Shoreline boundary Extensible Markup Language metadata (optional for .shp to open)	
BATH Shoreline.sbn	Shoreline boundary spatial index file for optimizing spatial queries (optional for .shp to open)	
BATH Shoreline.sbx	Shoreline boundary spatial index file for optimizing loading time (optional for .shp to open)	
BATH Shoreline.cpg	Shoreline boundary encoded plain text file describes .shp text charac- ter set (optional for .shp to open)	
BATH EBK.xml	Empirical Bayesian Kriging model parameters for interpolation of depth data points	
BATH Tracks.csv	Survey track	
BATH Volume.csv	Volume calculations	
BATH GE.kmz	Useable bathymetric map viewd in Google Earth	
BATH Map.pdf	Useable bathymetric map	
BATH.tif	Raster of interpolated depths	
HAB.shp	Habitat features classified polygons	
HAB Area.csv	Habitat area calculations	
HAB GE.kmz	Useable habitat map viewed in Google Earth	
Hab map.pdf	Useable habitat map	



Table 2: Maps produced from surveys collected prior to 2020: List of Variables Provided with the Bathymetric (BATH), Morphological Habitat (HABITAT) Map, Survey Tracks (BATH_Tracks), and Shoreline (BATH_shorePolyDigitized) File Types. 'DxxSITE' represents the NEON Domain number for each File Type, for example: D03BARC.

File Type	Header Name	Description	Data Type	Units
DxxSITE_HABITAT_YYYYMMDD_Area.csv	Frequency	Rate of occurance for each habitat type	int	NA
DxxSITE_HABITAT_YYYYMMDD_Area.csv	Habitat	Habitat type classification	String	NA
DxxSITE_HABITAT_YYYYMMDD_Area.csv	Area_m2	Calculated area for each habitat type	Real	meter
DxxSITE_BATH_YYYYMMDD_Tracks.csv	Object ID	Unique ID for each track	String	NA
DxxSITE_BATH_YYYYMMDD_Tracks.csv	Longitude	Geographic longitude	real	decimalDegree
DxxSITE_BATH_YYYYMMDD_Tracks.csv	Latitude	Geographic latitude	real	decimalDegree
DxxSITE_BATH_YYYYMMDD_Tracks.csv	Depth	Depth of water	int	meter
DxxSITE_BATH_YYYYMMDD_Volume.csv	Depth	Depth of water at set intervals	int	meter
DxxSITE_BATH_YYYYMMDD_Volume.csv	2d_area	2 dimensional surface area	int	squareMeter
DxxSITE_BATH_YYYYMMDD_Volume.csv	3d_depth	2 dimensional surface area plus slope	int	squareMeter
DxxSITE_BATH_YYYYMMDD_Volume.csv	Volume	Calculated water volume at a set depth interval	int	cubicMeter
DxxSITE_BATH_YYYYMMDD_ shorePolyDigitized.shp	Name	Lake and non-wadeable stream perimeter	string	NA
DxxSITE_BATH_YYYYMMDD_ shorePolyDigitized.shp	Shape_Leng	Lake and non-wadeable stream perimeter length	real	meter
DxxSITE_BATH_YYYYMMDD_ shorePolyDigitized.shp	Shape_Area	Lake and non-wadeable stream reach area	real	squareMeter



Table 3: Maps produced from surveys collected beginning in 2020: List of Variables Provided with the Bathymetric (BATH), Morphological Habitat (HABITAT) Map, Survey Tracks (BATH_Tracks), and Shoreline (BATH_shorePolyDigitized) File Types. 'DxxSITE' represents the NEON Domain number for each File Type, for example: D03BARC.

File Type	Header Name	Description	Data Type	Units
DxxSITE_HABITAT_YYYYMMDD_Area.csv	Habitat	Habitat type classifica- tion	String	NA
DxxSITE_HABITAT_YYYYMMDD_Area.csv	Area_m2	Calculated area for each habitat type	Real	meter
DxxSITE_BATH_YYYYMMDD_Tracks.csv	Object ID	Unique ID for each track	String	NA
DxxSITE_BATH_YYYYMMDD_Tracks.csv	Latitude_deg	Geographic latitude	real	decimalDegree
DxxSITE_BATH_YYYYMMDD_Tracks.csv	Longitude_deg	Geographic longitude	real	decimalDegree
DxxSITE_BATH_YYYYMMDD_Tracks.csv	BottomElevation_m	Depth of water	int	meter
DxxSITE_BATH_YYYYMMDD_Tracks.csv	BottomType	Bottom type classifica- tion PCA component number	int	NA
DxxSITE_BATH_YYYYMMDD_Volume.csv	Depth	Depth of water at set intervals	int	meter
DxxSITE_BATH_YYYYMMDD_Volume.csv	2d_area	2 dimensional surface area	real	squareMeter
DxxSITE_BATH_YYYYMMDD_Volume.csv	3d_area	2 dimensional surface area plus slope	real	squareMeter
DxxSITE_BATH_YYYYMMDD_Volume.csv	Volume	Calculated water volume at a set depth interval	real	cubicMeter
DxxSITE_BATH_YYYYMMDD_ shorePolyDigitized.shp	Name	Lake and non-wadeable stream perimeter	string	NA
DxxSITE_BATH_YYYYMMDD_ shorePolyDigitized.shp	Shape_Leng	Lake and non-wadeable stream perimeter length	real	meter
DxxSITE_BATH_YYYYMMDD_ shorePolyDigitized.shp	Shape_Area	Lake and non-wadeable stream reach area	real	squareMeter

The protocol dictates that each **locationID** is surveyed at least once every 5 years. One record is expected per **startDate** in bat_fieldData. Each **waypoint** may have multiple or no child records associated with **bathymetryDataType** (shoreline boundary, in-water feature, groundtruth targeted, groundtruth random) within the bat_pointcollection record, depending on whether a waypoint was collected during the survey. Each **recordingNumber** record from bat_sonarRecord is expected to have one to several child records for every survey track that is collected. One **dataFileName** and one **rawDataFileName** record will be created



in bat_resultsFile which contain the maps and raw data plus file extensions. However, duplicates and/or missing data may exist where protocol and/or data entry abberations have occurred; *users should check data carefully for anomalies before joining tables*.

bat_fieldData - > One record expected per **locationID**. Field data associated with the field level record. This table is linked to the bat_pointcollection and bat_sonarRecord tables through the **locationID**.

bat_pointcollection - > Up to several records expected per **waypoint**. Field data associated with the point level record.

bat_sonarRecord - > Several records expected per **recordingNumber**. A single parent location ID (recordingNumber) generates child recording number files.

bat_resultsFile - > One record per **siteID** and **startDate** combination. Contains basic information about the filenames and URLs used to access cloud-storage data product components that comprise the packaged bathymetric and habitat maps.

bat_AISsiteSurveyResultsFile - > One record per **siteIDxstartDate**. Contains basic information about the Aquatic Instrumental System site survey and URLs to access cloud-storage data products used to delineate hydraulic controls for the Stage-discharge rating curves (DP4.00133.001) and Continuous discharge (DP4.00130.001) data products for river sites and Toolik Lake inflow and outflow locations. These surveys will likely occur outside of a usual bathymetry bout and are not constrained by the same peak greenness window scheduling constraint.

3.9 Special Considerations

3.9.1 Downloading Bathymetric and Morphology Data

To download L4 bathymetric and morphology data packages:

- 1. Access the NEON data portal and select the desired data product (Bathymetry and Morphology Map), date range, and location (state and site).
- Download the dataset and open the .CSV file bat_resultsFile contained in the zipped folder. This .CSV file will contain a file named with the format "NEON.D##.SITE.DP1.00131.001.bat_resultsFile.YYYY-MM.basic.transitionDate.csv". Note that D## is the NEON Domain number and YYYY-MM is the year and month of the date range specified.
- 3. Links to the data storage location are provided in the **dataFileName** field.
- 4. For L4 data products, the links to the data storage location are provided in the **dataFileName** field.
- 5. Copy the URL provided in the **dataFileName** field into a web browser to initiate the download of the L4 survey data packages.
- 6. Users can also build scripts or use other tools that retrieve data from the NEON API and use the URL in different ways to retrieve the bathymetry data. The neonUtilities package, zipsByURI function, on CRAN is especially useful for these tasks (https://cran.r-project.org/web/packages/ neonUtilities/index.html).

Raw sonar and GPS data collected in the field are available upon request.



4 DATA QUALITY

4.1 Data Entry Constraint and Validation

Many quality control measures are implemented at the point of data entry within a mobile field data entry (Fulcrum) application or web user interface (UI). For example, data formats are constrained and data values controlled through the provision of dropdown options, which reduces the number of processing steps necessary to prepare the raw data for publication. An additional set of constraints are implemented during the process of ingest into the NEON database. The product-specific data constraint and validation requirements built into data entry applications and database ingest are described in the document NEON Raw Data Validation for Bathymetric and Morphological Maps (DP0.00132.001), provided with every download of this data product. Contained within this file is a field named 'entryValidationRulesForm', which describes syntactically the validation rules for each field built into the data entry application. Data entry constraints are described in Nicl syntax in the validation file provided with every data download, and the Nicl language is described in NEON's Ingest Conversion Language (NICL) specifications ([AD[12]).

4.2 Manual Data Processing Steps

Manual data processing transforms survey data from raw L0 data to an L4 data product. During this time QAQC procedures are performed which include a careful evaluation of field survey notes (contained in the metadata) that document errors that occurred during the survey. If survey notes indicate that L0 needs to be altered or deleted during post-processing these changes are addressed and subsequently expressed in the L4 product. Following data entry into a mobile application or web user interface, the steps used to process the data through to publication on the NEON Data Portal are detailed in the NEON Algorithm Theoretical Basis Document: OS Generic Transitions (AD[08]). Additional post-processing procedures are detailed in NEON Standard Operating Procedure: Post-Processing of Bathymetric and Side Scan Sonar Data from NEON Lakes and Non-Wadeable Streams (AD[09]).

4.3 Data Revision

All data are provisional until a numbered version is released. Annually, NEON releases a static version of all or almost all data products, annotated with digital object identifiers (DOIs). The first data Release was made in 2021. During the provisional period, QA/QC is an active process, as opposed to a discrete activity performed once, and records are updated on a rolling basis as a result of scheduled tests or feedback from data users. The Issue Log section of the data product landing page contains a history of major known errors and revisions.

4.4 Uncertainty

Spatial datasets are not a seamless representation of real-world phenomena.

Maps produced from surveys collected prior to 2020: A HumminBird 1198c SI Combo sonar with an XHS 9 HDSI 180 T transducer with down imaging (dual eam 200/83 kHz) and side imaging sonar (455/800 kHz)



are used to map NEON aquatic lakes and non-wadeable stream reaches during bathymetric and morphology surveys.

Maps produced from surveys collected beginning in 2020: A Biosonics MX aquatic habitat echosounder (200 kHz, single beam, down-looking) is used to map NEON aquatic lakes and non-wadeable stream reaches during bathymetric and morphology surveys.

A Trimble GeoXH 6000 or 7000 series GPS unit is used to collect GPS locations for the shoreline boundary, in-water features, and during ground truthing activities, throughout the bathymetric and morphology survey. Differential correction is applied during post-processing to improve GPS accuracy and reduce atmospheric errors by comparing the time signature at a fixed base station (typically CORS [Continuously Operating Reference Station]) nearby the rover file from the Trimble unit. The resulting file defines a horizontal and vertical accuracy using the root mean square error based on a 68% confidence level. NEON has aimed to utilize post-processed GPS positions that are within a horizontal and vertical precision of 10cm. Due to dense canopy at some sites and/or distance from base stations, not all GPS points surveyed fall within the desired range.



4.5 Quality Flagging

The **dataQF** field in each data record is a quality flag for known errors applying to the record. Please see below (Table 4) for an explanation of **dataQF** codes specific to this product.

Table 4: Options for dataQF and their explanations.

fieldName	value	definition	
dataQF	legacyData	Data recorded using a paper-based workflow that did not imple- ment the full suite of quality control features associated with the interactive digital workflow	

Records of land management activities, disturbances, and other incidents of ecological note that may have a potential impact are found in the Site Management and Event Reporting data product (DP1.10111.001)