

Ecosystem structure (DP3.30015.001)

Measurement

GeoTIFF raster of a Canopy Height Model with 1 m pixels whose value is the estimated height of the top of the vegetation canopy above the ground immediately below it, derived from the lidar point cloud data.

Collection methodology

NEON AOP instruments, including the full waveform LiDAR, are flown at 1000 m above ground level at 100 knots in flight lines that have 37% overlap. Data are acquired at a minimum density of 4 LiDAR shots per square meter in non-overlap areas. NEON AOP LiDAR returns are full waveforms, from which up to 5 points per shot may be discretized. All AOP L3 data products are distributed in 1 km by 1km tiles. NEON sites are flown once per year with a target of 90% of maximum greenness or higher and at a minimum of 3 of every 4 years. Flight coverage is a minimum of 10 km by 10 km and covers both NEON tower and observational sampling sites. Aquatic sites, as well as the terrestrial sites in Hawaii and Puerto Rico, are flown in the same fashion, but at reduced frequency.

For information about disturbances, land management activities, and other incidents that may impact data at NEON sites, see the [Site management and event reporting \(DP1.10111.001\)](#) data product.

Maintenance and calibration

The NEON AOP LiDAR is calibrated every winter between flight seasons. Calibration/validation flights for horizontal, vertical, and timing accuracy are conducted at the beginning and end of every flight season. Nominal runway flights are conducted in each domain flown during the flight season to ensure there is no accuracy drift. Field validation exercises collecting GPS points are typically conducted once per flight season.

Data processing and derivation

Raw discrete LiDAR data are processed to projected and corrected L1 LAZ point clouds in their original flight lines. First (highest elevation) LiDAR returns are gridded to 1 m pixels to create a digital surface model (DSM). Last (lowest elevation) returns are gridded to 1 m pixels to create a bare earth digital elevation model (DEM). Triangulation and interpolation are used to fill any gaps in DEM data if the LiDAR was unable to reach the ground. A raw canopy height model is created by subtracting the DEM from the DSM and preserving the values greater than 2 m in height (minimum detectable tree height). The finished CHM is created by filling any missed canopy-top pixels ("pits").

Data quality

Pixels with missing data are populated with a value of -9999. A quality report for each flight used in producing the data product, describing weather conditions and other data quality considerations during flight, is available for download via the L1 AOP LiDAR products. The L1 AOP LiDAR products also include uncertainty point clouds in LAZ format and processing quality report PDFs.

Documentation



[NEON Algorithm Theoretical Basis Document \(ATBD\): Ecosystem Structure](#)

NEON.DOC.002387vB | 1.4 MiB | PDF

For more information on data product documentation, see:
<https://data.neonscience.org/data-products/DP3.30015.001>

Citation

To cite data from Ecosystem structure (DP3.30015.001), see citation here:

<https://data.neonscience.org/data-products/DP3.30015.001>

For general guidance in citing NEON data and documentation, see the citation guidelines page:

<https://www.neonscience.org/data-samples/guidelines-policies/citing>

Contact Us

NEON welcomes discussion with data users! Reach out with any questions or concerns about NEON data:

[Contact Us](#)