NEON SENSOR COMMAND, CONTROL AND CONFIGURATION (C3) DOCUMENT: BIOLOGICAL TEMPERATURE

PREPARED BY	ORGANIZATION	DATE
Mike SanClements	FIU	03/20/2012
Hank Loescher	FIU	02/23/2012

APPROVALS	ORGANIZATION	APPROVAL DATE
Kate Thibault	SCI	07/07/2022

RELEASED BY	ORGANIZATION	RELEASE DATE
Tanisha Waters	CM	07/07/2022

See configuration management system for approval history.

The National Ecological Observatory Network is a project solely funded by the National Science Foundation and managed under cooperative agreement by Battelle. Any opinions, findings, and conclusions or recommendations expressed in this material are those of the author(s) and do not necessarily reflect the views of the National Science Foundation.

Change Record

REVISION	DATE	ECO #	DESCRIPTION OF CHANGE
A	06/22/2012	ECO-00417	Initial Release
B	07/07/2022	ECO-06849	• Revised logo and fine print

TABLE OF CONTENTS

1 DESCRIPTION

1.1 Purpose

This document specifies the command, control, and configuration details for operating a NEON sensor used for instrumental observations. It includes a detailed discussion of all necessary requirements for operational control parameters, conditions/constraints, set points, and any necessary error handling. All Level 0 Data Products generated by the sensor should be identified. The raw data are compensated by the DAS, but received at HQ for further processing as L0 unfiltered and uncorrected data product until its associated algorithms are applied to produce a QA/QC'd L1 data product in Standard Scientific Units.

1.2 Scope

The expectation is that the Apogee Instruments SI-111 IR Radiometer w/ Thermistor Custom Coefficient (NEON P/N: 0303220001; no firmware required) will be used to make the measurements of biological temperature (AD [01]). The reference document for the Apogee Instruments SI-111 IR Radiometer w/ Thermistor Custom Coefficient is RD [03].

This document specifies the command, control, and configuration that is needed for operating this sensor. It does not provide implementation details, except for cases where these stem directly from the sensor conditions as described here.

2 RELATED DOCUMENTS AND ACRONYMS

2.1 Applicable Documents

AD [01]	NEON.DOC.000001	NEON Observatory Design (NOD) Requirements
AD [02]	NEON.DOC.000291	NEON Configured Sensor List
AD [03]	NEON.DOC.005003	NEON Scientific Data Products Catalog
AD [04]	NEON.DOC.005005	NEON Level 0 Data Products Catalog
AD [05]	NEON.DOC.XXXXXX	Biological Temperature ATBD (TBW)

2.2 Reference Documents

RD [01]	NEON.DOC.000008 NEON Acronym List
RD [02]	NEON.DOC.000243 NEON Glossary of Terms
RD [03]	Campbell Scientific, Inc., Apogee Instruments, Inc. (2010). Instruction Manual: SI-111 Precision Infrared Radiometer. Campbell Scientific, Inc. (CSI) 815 West 1800 North Logan, Utah 84321 United States.

2.3 Acronyms

Acronym	Explanation
ATBD	Algorithm Theoretical Basis Document
C^3	Command, Control, and Configuration Document
SOP	Standard Operating Procedures
QA/QC	Quality Assurance/Quality Control
TIS	Terrestrial Instrument System
L0	Level 0
L1	Level 1
ENG	NEON Engineering group
CI	NEON Cyberinfrastructure group
DPS	NEON Data Products group
CVAL	NEON Calibration, Validation, and Audit Laboratory

2.4 Verb Convention

"Shall" is used whenever a statement expresses a convention that is binding. The verbs "should" and "may" express non-mandatory provisions. "Will" is used to express a declaration of purpose on the part of the design activity.

3 INTRODUCTION

The sensor configuration and sensor command and control described here are related to the biological temperature data product (FIU.0.0005.001) and sensor body temperature data product (FIU.0.0005.002) (AD[04]). A description of how sensor readings shall be converted to biological temperature in degrees Celsius is presented in the associated ATBD (AD[04]).

4 OVERVIEW OF SENSOR CONFIGURATION

The infrared broadband radiation biological temperature data product shall be unfiltered and uncorrected V. Sensor body temperature will be unfiltered and uncorrected Ω.

Table 1. Sensor configuration settings.

Parameter	Default Setting
Biological temperature: Acquisition rate	1 Hz
Sensor body temperature`: Acquisition rate	1 Hz
Data acquired from sensor	Biological temperature (mV); Sensor body temperature (mV)
Measurement mode	Run

5 COMMAND AND CONTROL

5.1 Error Handling

This sensor provides no error notification.

5.2 Sensor <device> Controls Specification

This sensor has no associated devices.

6 APPENDIX & BIBLIOGRAPHY

N/A